

Dual 11n WiFi Access Point, Ethernet Bridge, Repeater & MESH point for railways & heavy duty applications



Turbo roaming:
< 30 ms



C-Key READY



Top "C-Key" for
quick configuration
Save & Restore

- Dual radio IEEE 802.11n a/b/g (MIMO 3T3R), up to 2 x 300 Mbps radio bit rate
- MESH, WMM QoS, multiple SSID and centralized RADIUS security support
- Web based configuration, SNMP administration, serial port, C-Key, alarm contact
- 2-port auto-sensing Gigabit 10/100/1000 Base TX auto MDI/MDIX network interface
- Dual DC insulated power supply input (+9VDC to +140VDC), PoE IEEE 802.3at
- Shockproof & weatherproof IP 66 rugged aluminum enclosure

WLn-ABOARD series

IEEE 802.11n a/b/g
WiFi 2.4 / 5 GHz



5-YEAR WARRANTY



WLn-ABOARD is a rugged wireless broadband equipment designed for applications in road and railways transportation (CBTC architectures), depots, warehouses, agriculture, manufacturing floors, docks, distribution centers, shipyards and lumberyards ... it can be mounted in trains, tramways, trucks, freighter ships, forklifts, trailers, tractors or cranes, dumpers, mines for material handling, real-time information transmission (multiple CCTV cameras, VoIP phones ...), board to board, board to ground communications and ground infrastructure.

The two radio design makes it possible to use two separate networks for carriage bridging (5 / 5.4 GHz) and in-carriage communication (2.4 GHz) simultaneously without sacrificing speed; the turbo roaming feature allows lossless communication between APs during vehicle motion. Moreover, the dual radio system makes it possible to rely on a redundant network; redundancy is also possible between two devices.

It fulfills the most severe requirements in terms of operating environment: -25°C to +70°C (extended -40°C to +75°C, -55°C with optional PTC heater), shockproof and vibration proof, IP66 all weather seal rating for protection against dust, water projections and vapor.

WLn-ABOARD is certified for railway applications (EN 50155 [IEC 60571] / EN 50121-3-2 / EN 50121-4).

TECHNICAL CHARACTERISTICS OVERVIEW

Ethernet link	2-port Gigabit Ethernet 10/100/1000 auto-sensing, waterproof ultra-lock 8-point M12 connectors (CAT-6A), plug & play mode & auto MDI/MDIX cross-over
Serial port	One insulated RS422/485 serial port (waterproof ultra-lock M12 connector) for connection to the target equipment existing network
WiFi network	Compliant to the IEEE 802.11n a/b/g MIMO 3T3R, 2.4 / 5 / 5.4 GHz standards, dual radio system with redundancy
Data rate	Up to 2 x 300 Mbps
Radio channels	2.4 GHz: 13 channels in b/g, 7 channels in 11n / 5 GHz: 19 channels in a/h, 11 channels in 11n
Output power	Transmitter +20 dBm (TPC), +26 dBm with the WLn-RF400MW option
Sensitivity	Receiver -92 dBm for IEEE 802.11 a/g/n and -95 dBm for IEEE 802.11b
Antennas connections	Up to six 2.4 / 5 GHz MIMO antenna (not shipped with the product), N-type connectors, optional lightning surge protection
Modulation	OFDM: BPSK, QPSK, 16QAM, 64QAM / DSSS: DBPSK, DQPSK, CCK
Security	64/128 bits WEP, WPA-PSK, WPA2-PSK, IEEE 802.1x (centralized RADIUS authenticator & supplicant), MAC addresses filtering, SSID broadcast control
Modes	Access point to build a WiFi network infrastructure, Bridge to connect any Ethernet equipments to this network, MODBUS/TCP wireless gateway, repeater, MESH point (IEEE 802.11s), infrastructure, AD-HOC, bridge router, WMM QoS, multicast and IGMP-Snooping modes are fully supported; the 2 radios can be used to create a redundant link, roaming time less than 30 ms
Administration	Built-in WEB interface, the setup of the device is achieved using any web browser, SNMP agent, ACKSYS NDM, serial port, Telnet/SSH, CLI
Operating systems	Windows, Linux, UNIX as well as any operating system supporting TCP/IP
Signaling	LEDs signaling for radio quality, activity and status on each radio, Link 10/100/1000 and activity on each LAN port, TXD and RXD for the serial port, MAIN & AUX power supply, C-Key and product diagnostic
Alarms	Relay output warning: power failure, WLAN connection failure, Watchdog, over heating or user defined (SNMP); 1 FORM B solid state relay, 60V 0.15A (ultra-lock waterproof M12 connector)
Inputs	One insulated input for external device control (ultra-lock waterproof M12 connector)
Power supply	From +9VDC to +140VDC with 1500V insulation depending on models, dual input (ultra-lock waterproof M12 connector), optional PoE Plus (IEEE 802.3at) power supply with ground lug
Consumption	16W typical power consumption (21W maximum with two high power radio cards)
Dimensions & weight	Shockproof, vibration proof rugged aluminum enclosure, (L: 160 x W: 220 x H: 35mm), 1200g
Standards	EN 301489-17 & EN 61000-6-2 (CEM), IP66 seal rating, UTAC E2 (2004/104), EN 50155 (IEC 60571), EN 50121-3-2, EN 50121-4 (railways ground & rolling stock)
Environment	Operating temperature : -25°C to +70°C or extended -40°C to +75°C (HR 0-99%), storage : -40°C to +100°C Optional PTC heater for -55°C operation (additional 24VDC 15W power supply required)

References to order

WLn-ABOARD [Hx]	WiFi Access Point, 2-port Ethernet Bridge, Repeater & MESH point (IEEE 802.11n a/b/g) for automotive applications, dual DC power input from +9VDC to +72VDC, POE IEEE 802.3at, one set of 2 meters cables (Ethernet & power cable), IP66
WLn-ABOARD/24 [Hx]	Insulated power supply: +9VDC to +36VDC (24VDC nominal), POE not available
WLn-ABOARD/N [Hx]	<i>Power supply: +9VDC to +72VDC, POE not available</i>
WLn-ABOARD/48 [Hx]	<i>Insulated power supply: +36VDC to +75VDC (48VDC nominal), POE not available</i>
WLn-ABOARD/72 [Hx]	<i>Insulated power supply: +44VDC to +110VDC (72VDC nominal), POE not available</i>
WLn-ABOARD/110 [Hx]	<i>Insulated power supply: +66VDC to +154VDC (110VDC nominal), POE not available</i>
C-Key_M2	Save / Restore configuration key for the WLn-ABOARD
WLg-ANT-LSP-N	Lightning Surge Protector 50 Ohms N-Type antenna 5 KA (0-6 GHz)
WLg-ANT-TERM-N	50 Ohms antenna terminator
WLn-PTC	PTC heater for -55°C cold start and operation
PWS-24-UNI-M12	AC power supply 110-240VDC input (24VDC 25W) with 2 meters M12 to stripped cable for WLn-ABOARD and WLn-ABOARD/N

Hx means high power version and extended temperature range (-40°C to +75°C), x = 4 for 400mW
In blue means products that are not kept in stock, MOQ is required for these models

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and