

		PoE Injector & Splitter				Racks & Chassis		
		 PoE+	 PoE+	 PoE+				
		ET-INJ90	ET-INJ60	ET-INJ30	ET-SPT12V	MR-C10	ET-C12	EC-C14
Ethernet	Port (RJ45)	2 x 10/100/1000-T	2 x 10/100/1000-T	2 x 10/100/1000-T	2 x 10/100/1000-T	—	—	—
	PoE port	1 (LTPoE++ 90W)	1 (LTPoE++ 60W)	1 (30W)	—	—	—	—
	PD port	—	—	—	1	—	—	—
Fiber	Port	—	—	—	—	—	—	—
	Connector	—	—	—	—	—	—	—
	Max. Distance	—	—	—	—	—	—	—
	Wavelength	—	—	—	—	—	—	—
Electrical	Input Power	48~57 VDC	48~57 VDC	48~57 VDC	—	110~240VAC, 50/60Hz	110VAC / 60Hz 220VAC / 50Hz	100~240VAC, 50/60Hz
	Output Power	—	—	—	Max. 20W 12VDC	12VDC@3.34A	5VDC@25A	5VDC@12A
	Maximum Power Consumption	95W	65W	35W	25W	40W	125W	60W
Mechanical	No. of Empty Slots	—	—	—	—	10 (Units)	12 (Units)	14 (Units)
	Dimension (W*D*H)	31 x 80 x 96mm				478 x 136 x 44mm	435 x 185 x 132mm	490 x 230 x 90mm
	Weight	0.2Kg	0.2Kg	0.2Kg	0.25Kg	0.7Kg	3.1Kg	3.5Kg
	Case	Aluminum				—	—	—
	Mounting	Din-rail / Wall-mount				19" 1U Rack-mount	19" 3U Rack-mount	19" 2U Rack-mount
Environmental	Operating Temperature	-40°C~75°C (-40°F~167°F)				-40°C~75°C (-40°F~167°F)	-20°C~60°C (-4°F~140°F)	-10°C~55°C (14°F~131°F)
Regulatory		CE, FCC				—	—	—